



BLACK ASPHALT ASPHALT FENCE & BARN COATING

Product Description:

Black Asphalt is a very heavily bodied coating designed for application on wood fences and barns. When properly applied this product gives 1 to 3 years weather protection. Black Asphalt initially goes on with a high gloss but quickly flattens to a brownish black color. This product is also popular on run in sheds, barn roofs and tanks.

Performance Information:

- * 1 to 3 year durability on fences
- * Good weather protection for fences
- * Safe around valuable live stock
- * Excellent adhesion to all fence surfaces - can be applied over creosote and CCA salt treated lumber

Uses:

- * Plank Fences
- * Barns
- * Metal Roofs
- * Run In Sheds
- * Farm Buildings

Characteristics:

- * Color - Black with brown cast
- * Finish - Flat
- * Drying time - @ 77F and 50% relative humidity
To touch: 1 to 2 days
Product will gain hardness over next several weeks
- * Flash point - 105F (PMCC)
- * Viscosity - 115KU @ 77F
- * Recommended coverage rate:
3 & 4 board plank fence - 10 to 12 running feet per gallon (both sides)
1 board plank fence - 18 running feet per gallon (both sides)
Barns - 100-150 sq. feet per gallon on smooth surfaces
Less than recommended applications will see a marked difference in durability
- * Weight per gallon - 7.9 lbs.
- * Package - 5 gal pails, 55 gal drums, bulk

Application:

- * Apply to clean fence with brush, roller or spray.
- * Airless spray requirements:
Rating - 1.0 gallons per minute minimum
Pressure - maximum (3000psi)
Filter - none
Tip - .025" to .031"

- * For spray application product must be heated to approximately 100F before being applied.

WARNING - product is combustible and will burn. Use only UL listed heating equipment.

- * **CAUTION** - Material will ignite upon contact with ignition source.
- * Allow new wood to weather 1 to 3 months in order to reduce moisture content
- * Will not freeze
- * Follow recommended coverage rates for best results
- * Clean up with mineral spirits