



FIBERED ALUMINUM FIBERED ALUMINUM ROOF COATING

Product Description:

Fibered Aluminum is a premium grade fibered aluminum roof coating formulated to seal and waterproof a variety of roof and outside wall surfaces. The aluminum finish helps reflect damaging sunlight and also reduces operating costs by keeping interior temperatures cooler during summer months which reduces air conditioning costs. This product can be used on built up roofs, composition roofs, metal roofs, shingled roofs as well as other roof surfaces. Commercial spray application is possible using large spray tips.

Uses:

- * Metal Roofs
- * Mobile Home Roofs
- * Built Up Roofs
- * Shingled Roofs
- * Composition Roofs
- * Outside Wall Surfaces

Performance Information:

- * Premium quality contractor grade coating
- * Helps stop leaks
- * Reflects damaging sunlight
- * Extends life of roof
- * Reduces cooling costs
- * Easy to apply with roof brush or spray
- * Can be used on a variety of roof surfaces

Characteristics:

- * Color - Metallic aluminum
- * Components - One
- * Flash point - 105F (PMCC)
- * Recommended spread rate:
75 to 100 sq.ft. per gallon
- * Dry time - @ 77F and 50% relative humidity
To touch: 6 hrs.
Tack free: 12 hrs.

Application:

- * Method - Roof brush, mop or commercial spray
do not roll
- * Airless spray :
Rating - 2.5 gallons per minute minimum
Pressure 3000psi
Tip 0.041" to 0.055"
Filter - none
- * Application temperature - Above 45F
- * Mix thoroughly before application to uniform consistency
- * No thinning recommended
- * Surface preparation - Surface must be clean and dry. Remove oil, dust, dirt, loose rust, peeling paint or other contaminants to ensure good adhesion.
- * Rust Treatment - An appropriate metal primer will extend the life of this coating and retard corrosion on rusted metal roofs
- * DO NOT USE on dead flat or gravel roofs
- * Clean up with mineral spirits

