



JETCOAT BLACK OIL-BASED FENCE & BARN PAINT

Product Description:

A premium quality oil-based paint formulated especially for fences and barns. It is easy to apply and offers long term durability on new or weathered surfaces. This product offers a better finish than more economical black paints and is therefore often used in high visibility areas where the best available product is required. On new lumber or metal this product is self priming. Can also be used on interior barn surfaces, silo, sheds, concrete or properly prepared metal.

Performance Information:

- * Top quality fence and barn paint
- * Linseed-oil/alkyd formulation for durability and flexibility
- * Excellent weather protection
- * Quick positive dry time
- * Excellent color retention
- * Safe around valuable livestock

Uses:

- * Plank Fences
- * Barns
- * Barn Stalls
- * Run In Sheds
- * Loading Areas and Chutes
- * Gates

Characteristics:

- * Color - Black
- * Finish - Semi-gloss, 30 to 50 units at 60 degrees
- * Drying time - @ 77F and 50% relative humidity
 - To touch: 4-6 hours
 - Dry : 8 hours
 - Re-coat : after overnight dry
- * Flash point - 105F (PMCC)
- * Viscosity - 90KU
- * Recommended coverage rate:
 - 3 & 4 board plank fence - 16 running feet per gallon (both sides)
 - 1 board plank fence - 26 running feet per gallon (both sides)
 - Barns - 325 sq. ft per gallon on smooth surfaces
- * Shelf life - 2 years (unopened, proper agitation)
- * Package - 5 gal pails, 55 gal drums
- * VOC - less than 380 grams/liter

Application:

- * Apply to clean dry fence with brush, roller or spray
- * Airless spray requirements:
 - Rating - 0.5 gallons per minute minimum
 - Pressure - 1800 to 3000psi
 - Filter - 30 to 60 mesh
 - Tip - .017" to .021"
- * Stir thoroughly before applying
- * Fence preparation - For greatest durability make sure fence is scraped thoroughly by removing any peeling or flaking paint
- * Allow new wood 1 to 3 month in order to reduce moisture content
- * Application temperature - above 40F
- * Follow recommended coverage rate for best results
- * No thinning recommended
- * Clean up with mineral spirits